

FXGS22

10G Wired XGSPON ONT



Function

- WAN Type: IPoE / Static IP / PPPoE / Bridge
- Protocols: IPv4 / IPv6 dual stack
- Support VLAN 1-4094
- IGMP v2 (RFC 2236) & IGMP v3 (RFC 3376)
- Support IGMP Snooping & Proxy
- T.30/T.38/G.711 FAX mode
- DTMF & RFC2833
- Application: DDNS/ NAT/ VPN/ UPnP/ SNTP
- Support WAN/LAN access the Telnet & HTTP
- Support Parental Controls
- Security: Firewall, IP/ MAC /URL Filter
- Support TR-069 Remote Management Protocol

XGSPON Features

- Class B+ Optical System
- Maximum Receive Sensitivity: -8 dBm
- Minimum reception sensitivity: -28 dBm
- Wavelengths: US 1270 nm / DS 1577nm
- Speedtest: DS/US=8.5Gbps /8.5Gbps
- Support ITU-T.984.X / ITU-T G.988 Standard
- Authentication: SN / LOID / Ploam password
- Support OLT: HUAWEI / ZTE / Fiberhome / NOKIA

Specification

Hardware Performance	
Chipset	AN7581
FLASH	128MB
SDRAM	512MB DDR3
Interface	1*10GE+1*GE+2*RJ11
Button	1*Reset+1*ON//OFF
Power Supply	12V/1.5A
LED	Power+PON+LOS+NET+LAN+10G+TEL1+TEL2
Others	
Packing list	XGSPON Fiber ONT 1.0 Meter Cat5e network cable User Manual
Power input	12V/1.5A Any standard
Working Environment	Operating temperature: 0°C to 45°C Storage temperature: -20°C to 70°C Operating humidity: 10% to 90% RH without condensation Storage humidity: 5% to 90% RH without condensation

ALTI-LINK

ALTI-LINK COMMUNICATION CO., LIMITED

Room 310, Building 4, Dongjiu Innovation Technology Park,

No#76 Bulan Road, 518057, Shenzhen, P.R.China

Email: inquiry@alti-link.com

Copyright ©2014~2024 Alti-link All Rights Reserved.Specifications are subject to change without notice.